

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard.
9 CFR 1910.1200. Standard must be consulted for specific
requirements.

U. S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1210-0072

IDENTITY (AS USED ON LABEL AND LIST)***Trojan Beta-Z Wood Sealer #60-65***

NOTE: BLANK SPACES ARE NOT PERMITTED. IF
ANY ITEM IS NOT APPLICABLE, OR NO
INFORMATION IS AVAILABLE THE SPACE MUST BE
MARKED TO INDICATE THAT.

SECTION I**MANUFACTURER NAME:**

ENVIROSAFE MANUFACTURING CORP.

East Coast: 7634-B Progress Cir. * **West Coast:** 817 Benton Way
Melbourne, FL 32904 Wenatchee, WA98801

CHEMTREC COMPANY CODE: C937**EMERGENCY PHONE NUMBER**

CHEMTREC (800) 424-9300 Domestic
(703) 527-3887 International

TELEPHONE NUMBER FOR INFORMATION

1-800-800-5737

DATE PREPARED/UPDATED

01/09/2002

01/12/2008

D.O.T. Hazard Class: Non-Hazardous-Not Regulated

SECTION II - Hazardous Ingredients / Identity Information

| Hazardous Components (Specific Chemical Identity): Common Name: | OSHA PEL | ACGH TLV | Other Limits Recommended | % |
|---|----------|----------|--------------------------|---|
| <i>No hazardous Materials to report</i> | | | | |
| | | | | |

N/E – Not Established

N/A – Not Applicable

SECTION III – Physical / Chemical Characteristics

BOILING POINT:

110⁰ C/-19%

VAPOR PRESSURE (MM HS):

N/A

VAPOR DENSITY (AIR = 1):

N/A

APPEARANCE AND ODOR:

Translucent Liquid

V.O.C.: (Extremely Low)

11.67 g/L

SPECIFIC GRAVITY (H2O = 1):

1.01

FREEZING POINT:

Approx. 32⁰ F

EVAPORATION RATE (Butyl Acetate=1):

N/A

SOLUBILITY IN WATER:

*Complete***SECTION IV – Fire and Explosion Hazard Data**

FLASH POINT (METHOD USED): None

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA: Non-Flammable

SPECIAL FIRE FIGHTING PROCEDURES: None

UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: None

FLAMMABLE LIMITS: None

SECTION V – Reactivity Data

STABILITY:

STABLE: X

UNSTABLE: _____

INCOMPATIBLE (MATERIALS TO AVOID) ORGANICS ALKALI & ACID PRODUCTS

HAZARDOUS DECOMPOSITIONS OR BYPRODUCTS: NE

HAZARDOUS POLYMERIZATION : MAY OCCUR _____ WILL NOT OCCUR: X

CONDITIONS TO AVOID: N/A

SECTION VI – Health Hazard Data

ROUTE(S) OF ENTRY: INHALATION? Yes

SKIN? Yes

INGESTION? Yes

Summary: Data for this material has been used to estimate its environmental impact. It has the following properties: A low biochemical oxygen demand and little potential to cause oxygen depletion in aqueous systems, a low potential to affect aquatic organisms, a low potential to affect the germination and orderly growth of some plants. When diluted with a large amount of water, this material released directly or indirectly into the environment is not expected to have a significant impact.

SECTION XI - TRANSPORTATION INFORMATION:

DOT (USA) STATUS: Not regulated

TDG (CANADA) STATUS: Not regulated

AIR - INTERNATIONAL CIVIL AVIATION ORGANIZATION ICAO - ICAO STATUS: Not regulated

SEA - INTERNATIONAL MARITIME DANGEROUS GOODS (IMDG) - IMDG STATUS: Not regulated

SECTION XII - REGULATORY INFORMATION:

This document has been prepared in accordance with the MSDS Requirements of the OSHA HAZARD COMMUNICATION STANDARD 29 CF4 1910. 1200

OSHA HAZARDOUS CHEMICAL(S): None

CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER TOXIC ENFORCEMENT ACT OF 1986):

MATERIAL(S) KNOWN TO THE STATE TO CAUSE CANCER: None materials known to the state to

Cause adverse reproductive effect: None

MASSACHUSETTS SUBSTANCE LIST: None

NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST: None

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR RESULTS TO BE OBTAINED FROM THE USE THEREOF.

VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEETS. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSON PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN THE USE OF THIS MATERIAL.