

ENVIROSAFE MANUFACTURING CORP.

Product Data: **Easy Brick Cleaner** **#40-46**

Product Description	A unique formulation that cleans and restores brick surfaces. Use on stucco, block, brick and brick pavers, especially red or dark colored brick.
Typical Uses	For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, brick pavers, stucco, cinder block or any masonry surface that needs to be cleaned of dirt and grime.
Product Advantages	Easy Brick Cleaner is: * Fast * Easy to apply * Water clean-up * No Solvents * Will not harm or deteriorate masonry surfaces when used properly * Removes even stubborn stains * Water Soluble
Color	Orangy Yellow
Physical Constants	<p>Specific Gravity: (H2O=1) 1.2 @ 24 Deg C.</p> <p>Solubility in Water: Excellent</p> <p>Evaporation Rate: Same as water</p> <p>pH: 1.0 (Corrosive)</p> <p>Storage: 40-100 deg. F</p>
Coverage Rate	250-300 sq.ft./gal. depends on roughness of surface & degree of soil
Sold in	<p>1-Gallon Bottles</p> <p>5-Gallon Pails</p> <p>55-Gallon Drums</p>



Envirosafe Manufacturing Corp.
 7634-B Progress Circle
 W. Melbourne, FL 32904

Phone: 800-800-5737
 Fax: 321-733-0255
 Email: sales@envirosafemfg.com
 Www.envirosafemfg.com

Products that get the job done!

EASY BRICK CLEANER™ #40-46

Application Instructions:

ALWAYS TEST ON SURFACES PRIOR TO APPLICATION!

SURFACE PREPARATION AND APPLICATION

NOTE: Wear gloves and goggles to protect from splashing.

1. Wash surface with **ENVIRO-CLEAN DEGREASER** to remove all surface dirt. Rinse well with water.
2. Water all grass and shrubs well before starting. While damp use a Pump Sprayer to apply **EASY BRICK CLEANER** at a rate of 200-250 sq.ft./gal.
3. Let stand for approximately 5 - 10 minutes, depending on the extent of the soil and stain and the durability of the surface treated will determine the length of time before rinsing.
4. Scrub with a nylon bristle stiff broom or wire brush on any stubborn stains. Pressure wash off with minimum 3000 psi.

We recommend you wear OSHA Complaine chemical gloves, eye protection and rubber boots for protection.

6. Rinse with plenty of water. Always have a water source to wash off product and equipment
7. **Clean-Up:** Clean all equipment with **Enviro-Clean Degreaser Cleaner** and water.
8. Apply **Trojan Masonry Sealer** to waterproof surface and to keep stains from penetrating surface.
9. For best results use a pressure washer at a minimum of 3000 psi.

Safety: Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. All products are offered and sold subject to Envirosafe Manufacturing Corporations Standard Conditions of Sale. Published

technical data and instructions are subject to change without prior notice.

LIMITATIONS

Apply in good weather when air and surface temperatures are above 45 degrees Fahrenheit and surface temperature is at least 5 degrees Fahrenheit above the dew point. For optimum application properties, materials should be between 70 to 100 degrees Fahrenheit prior to application. Maintain unused material in closed containers in protected storage at 40 - 100 degrees Fahrenheit.

Do not store material in strong sunlight

RECOMMENDED USES:

- | | | |
|------------|------------|-----------------------|
| *Walls | *Buildings | *Industrial Buildings |
| *Sidewalks | *Homes | *Commercial Buildings |
| *Driveways | *Streets | *Shopping Centers |
| *Patios | | |