

ENVIROSAFE MANUFACTURING CORP.

Product Data: **Efflorescence Remover** **#40-43**

Product Description	A fluid applied cleaner that removes efflorescence from concrete, masonry, brick and block surfaces
Typical Uses	For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, brick pavers, stucco, cinder block or any masonry surface that has efflorescence.
Product Advantages	Efflorescence Remover is: * Economical * Fast and Easy to Apply * No Solvents * Easy clean-up * Water Soluble * Removes even Stubborn Efflorescence * Will not harm or deteriorate masonry surfaces when used properly
Color	Yellow
Physical Constants	<p>Specific Gravity: (H2O=1) 1.2 @ 24 Deg C. Solubility in Water: Excellent Evaporation Rate: Same as water pH: 1.0 (Corrosive) Storage: 40-100 deg. F</p>
Coverage Rate	250-300 sq.ft./gallon (depends on roughness of surface & degree of efflorescence)
Sold in	<p>1-Gallon Bottles 5-Gallon Pails 55-Gallon Drums</p>



Envirosafe Manufacturing Corp.
 7634-B Progress Circle
 W. Melbourne, FL 32904

Phone: 800-800-5737
 Fax: 321-733-0255
 Email: sales@envirosafemfg.com
 Www.envirosafemfg.com

*Products that get the
job done!*

EFFLORESCENCE REMOVER™ #40-43

Application Instructions:

Always test on surfaces prior to application.

Surface Preparation and Application:

1. Use **Enviro-Clean Degreaser Cleaner™** to clean concrete, brick, stone, paver, or mortar joint to remove any surface efflorescence.
2. Water all grass and shrubs well before starting. Apply **Efflorescence Remover** by pump sprayer to surface until "foam" begins to appear. Foam only appears when efflorescence is present.
3. Wait 5 minutes, reapply as necessary, mechanically agitate and use Turbo Zero tip attachment for pressure washer to remove efflorescence using 3000 psi.
4. Re-apply to areas where "foam" appears and continue to reapply until foam no longer appears after application.
5. Pressure wash area completely using minimum pressure of 3000 psi.

Clean up: Clean all equipment immediately after use with warm, soapy water.

Note: For an excellent penetrating sealer, apply **Trojan Masonry Sealer™** to dry surfaces.

Special Note:

1. If efflorescence is more than just powder use **Envirosafe Rust/Stain Remover™**. Rinse thoroughly.
2. Applying **Trojan Masonry Sealer™** to seal the surface and prevent future efflorescence.

Safety: Safe, storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling.

Limitations: Apply in good weather when air and surface temperatures are above 45 degrees F. and surface temperatures is at least 5 degrees F. above the dew point. For optimum application properties, materials should be stored at 70 - 100 degrees F. prior to application. Maintain unused material in closed containers in protected storage at 40-100 degrees F. **Do not store in strong sunlight.**

Notice: The technical data contained herein are true and accurate to the best of our knowledge. All products are offered and sold subject to Enviro-safe Manufacturing Corporations Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.

RECOMMENDED USES AND ADVANTAGES

***Masonry**

***Block - Brick**

***Fast and Effective**

***Non-Flammable**

***Non-Carcinogenic**

***Biodegradable**