



Environmentally safe products that
"Get the Job Done"

(800) 800-5737



(866) 874-8070

Product Data:

NuLook Concrete Cleaner #40-44

Product Description	A fluid applied cleaner that removes dirt, oil and stains from concrete, light colored brick and stucco surfaces restoring that "New Look" finish.
Typical Uses	For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, light colored brick pavers, stucco, cinder block.
Product Advantages	NuLook Concrete Cleaner is: * Economical * Fast * Effective * Non-Flammable * Non-Toxic * Easy clean-up * Biodegradable * Water Soluble * No Solvents * Will not harm or deteriorate masonry surfaces when used properly
Color	Yellow
Physical Constants	Specific Gravity: (H ₂ O=1) 1.2 @ 24 Deg C. Solubility in Water: Soluble Evaporation Rate: Same as water pH: 1.0 (Corrosive) Storage: 40-100 deg. F Evaporation Rate: Slower than water Viscosity: More than water Method of Application: Sprayer and pressure washer
Coverage Rate	250-300 sq. ft./gallon (depends on roughness of surface & degree of soil)
Sold in	1-Gallon Bottles 5-Gallon Pails 55-Gallon Drums



Before & After sidewalk cleaning

Parking lot Cleaning with NuLook



Envirosafe Manufacturing Corp.™
 East Coast: 7634-B Progress * West Coast: 817 Benton Way
 Melbourne, FL 32904 Wenatchee, WA 98801

Web Sites
www.envirosafemfg.com
www.eco-wares.com

Products that get the job done!

NU LOOK CONCRETE & MASONRY CLEANER #40-44

APPLICATION INSTRUCTIONS:

Always test on surface prior to application

LIMITATIONS: Apply in good weather when air and surface temperature are above 45 deg. F and surface temperature is at least 5 deg. F above the Dew Point. For optimum application properties, materials should be between 70-90 deg. F prior to application. Maintain unused material in closed containers in protected storage at 40-90 deg. F **out of direct sunlight.**

SURFACE PREPARATION:

1. Water all surrounding grass and shrubs well before starting application of **NuLook Concrete Cleaner**. Clean all oil and grease off surface using **Enviro Clean Degreaser**. Apply **NuLook Concrete Cleaner** with a plastic garden pump sprayer (Hudson Type) or low pressure sprayer.
2. Allow at least 4-8 minutes for **NuLook Concrete Cleaner** to deep clean the pores of the concrete depending on the extent of the soiling and the durability of the surface. (This is why **Testing** is important)
3. Agitate concrete surface using a stiff nylon brush, broom or rotating concrete scrubber and 3000 psi pressure washer.
4. Power wash away all dirt and remaining **NuLook** and rinse well. If rust stains are present, apply **Rust Stain Remover** according to the instructions, pressure wash off and re-apply **NuLook Concrete Cleaner** to achieve the whitening.
5. Scrub with a stiff nylon bristle broom or wire brush on any stubborn stains. Pressure wash off with minimum 3000 psi. We recommend you wear OSHA Compliance chemical gloves, eye protection and rubber boots.
6. Rinse with plenty of water. Rinse equipment immediately after use.
7. **Clean-up:** Clean all equipment with **EnviroClean Degreaser** and water.
8. Apply **TROJAN MASONRY SEALER** to seal surface and to keep future stains from penetrating surface.

Safety: Safe Storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling

Notice: The technical data contained herein is true and accurate to the best of our knowledge. All products are offered and sold subject to **Envirosafe Manufacturing Corporations** Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.