

ENVIROSAFE MANUFACTURING CORP.

Product Data: **NuLook Concrete Cleaner** **#40-44**

Product Description	A fluid applied cleaner that removes dirt, oil and stains from concrete and light colored brick and stucco surfaces restoring that "New Look" finish.
Typical Uses	For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, light colored brick pavers, stucco, cinder block.
Product Advantages	NuLook Concrete Cleaner is: * Economical * Fast * Effective * Non-Flammable * Non-Toxic , * Easy clean-up * Biodegradable * Water Soluble * No Solvents * Will not harm or deteriorate masonry surfaces when used properly
Color	Yellow
Physical Constants	<p>Specific Gravity: (H2O=1) 1.2 @ 24 Deg C.</p> <p>Solubility in Water: Excellent</p> <p>Evaporation Rate: Same as water</p> <p>pH: 1.0 (Corrosive)</p> <p>Storage: 40-100 deg. F</p> <p>Evaporation Rate: Slower than water</p> <p>Viscosity: More than water</p> <p>Method of Application: Sprayer</p>
Coverage Rate	250-300 sq.ft./gallon (depends on roughness of surface & degree of soil)
Sold in	<p>1-Gallon Bottles</p> <p>5-Gallon Pails</p> <p>55-Gallon Drums</p>



Envirosafe Manufacturing Corp.
7634-B Progress Circle
W. Melbourne, FL 32904

Phone: 800-800-5737
Fax: 321-733-0255
Email: sales@envirosafemfg.com
Www.envirosafemfg.com

*Products that get the
job done!*

NU LOOK CONCRETE & MASONRY CLEANER™ #40-44

APPLICATION INSTRUCTIONS

Always test on surface prior to application.

SURFACE PREPARATION AND APPLICATION

1. Water all grass and shrubs well before starting. Apply **Nu Look Concrete Cleaner** with a plastic garden pump sprayer (Hudson Type) or low pressure pump.
2. Allow at least 4 - 8 minutes for **Nu Look Concrete Cleaner** to deep clean the pores.
3. Agitate concrete surface using a **RotoBlaster Concrete Scrubber**.
4. Power Wash and rinse thoroughly using 3000 psi.
5. If Applicator has rust stain on the concrete surface, apply **Envirosafe Rust Stain Remover**, allow at least 4 - 8 minutes. Agitate, rust stain with brush or broom. Pressure Wash and rinse thoroughly at 3000 psi.
6. After the cleaning process, allow to dry and apply penetrating **Trojan Masonry Sealer** to provide a permanent waterproof barrier for masonry surfaces.
7. For equipment clean up, use our multi purpose **Enviro Clean Degreaser Cleaner** with water. This product is a concentrate and is effective for ongoing maintenance.
8. OSHA recommends using goggles, rubber gloves and rubber boots when applying this product.

Cleanup: Clean all equipment immediately after use with warm, soapy water.

Safety: Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling.

Limitations: Apply in good weather when air and surface temperatures are above 45 degrees Fahrenheit and surface temperature is at least 5 degrees Fahrenheit above the dew point. For optimum application properties, material should be stored at 70 - 100 degrees Fahrenheit prior to application. Maintain unused material in closed containers in protected storage at 40 - 100 degrees Fahrenheit . **DO NOT STORE IN STRONG SUNLIGHT.**

Notice: The technical data contained herein are true and accurate to the best of our knowledge. All products are offered and sold subject to Envirosafe Manufacturing Corporations Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.

RECOMMENDED USES

- | | |
|--------------------|---------------------------------|
| * Sidewalks | * Driveways |
| * Buildings | * Slabs |
| * Ramps | * Car Dealerships Repair Stalls |
| * Auto Body Shops | * Gas Stations |
| * Shopping Centers | * Streets |