



(800) 800-5737



(866) 874-8070

Product Data: **Red Clay Stain Remover** **#40-45**

Product Description	A unique formulation that removes red clay stains from concrete, masonry, brick and block surfaces for areas of the country that have red clay.
Typical Uses	For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, brick pavers, stucco, cinder block or any masonry surface that has stains, particularly rust stains.
Product Advantages	Red Clay Stain Remover for Masonry is: *Fast and Easy to Apply * Easy clean-up * No Solvents * Water Soluble * Removes even stubborn stains * Will not harm or deteriorate masonry surfaces when used properly
Color	Clear Red
Physical Constants	<p>Specific Gravity: (H2O=1) 1.2 @ 24 Deg C. Solubility in Water: Excellent Evaporation Rate: Same as water pH: 1.0 (Corrosive) Storage: 40-100 deg. F Evaporation Rate: Slower than water Viscosity: More than water Method of Application: Sprayer</p>
Coverage Rate	250-300 sq. ft./gallon (depends on roughness of surface & degree of staining)
Sold in	1-Gallon Bottles 5-Gallon Pails 55-Gallon Drums



Red clay stained

Cleaned of red clay with **Red Clay Stain Remover**

Envirosafe Manufacturing Corp.™
East Coast: 7634-B Progress * **West Coast:** 817 Benton Way
 Melbourne, FL 32904 Wenatchee, WA 98801
 (800) 800-5737 (509) 662-9204

Web Sites
www.envirosafemfg.com
www.eco-wares.com

Products that get the job done!

RED CLAY STAIN REMOVER™ #40-45

LIMITATIONS

Apply in good weather when air and surface temperatures are above 45 degrees Fahrenheit and surface temperature is at least 5 degrees Fahrenheit above the dew point. For optimum application properties, materials should be between 70 to 100 degrees Fahrenheit prior to application. Maintain unused material in closed containers in protected storage at 40 - 100 degrees F.

SURFACE PREPARATION AND APPLICATION

NOTE: Use gloves and goggles.

1. Water bordering grass and shrubs before starting. Using hand pump sprayer, apply **Red Clay Stain Remover**.
2. Let stand for approximately 3 to 5 minutes.
3. Scrub any stubborn stains with brush.
4. Pressure wash off with minimum 3000 psi.

Cleanup: Clean all equipment immediately after use with warm soapy water.

Safety: Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. All products are offered and sold subject to Envirosafe Manufacturing Corporations Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.