

ENVIROSAFE MANUFACTURING CORP.

Product Data: **Rust/Stain Remover** **#40-41**

Product Description	A unique formulation that removes rust and stains from concrete, masonry, brick and block surfaces
Typical Uses	For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, brick pavers, stucco, cinder block or any masonry surface that has stains, particularly rust stains.
Product Advantages	Rust Stain Remover for Masonry is: *Fast and Easy to Apply * Easy clean-up * Water Soluble * Removes even stubborn stains * No Solvents * Will not harm or deteriorate masonry surfaces when used properly
Color	Orangy Yellow
Physical Constants	<p>Specific Gravity: (H2O=1) 1.2 @ 24 Deg C.</p> <p>Solubility in Water: Excellent</p> <p>Evaporation Rate: Same as water</p> <p>pH: 1.0 (Corrosive)</p> <p>Storage: 40-100 deg. F</p> <p>Evaporation Rate: Slower than water</p> <p>Viscosity: More than water</p> <p>Method of Application: Sprayer</p>
Coverage Rate	250-300 sq.ft./gallon (depends on roughness of surface & degree of staining)
Sold in	1-Gallon Bottles 5-Gallon Pails 55-Gallon Drums



Before and After cleaning with **Rust Stain Remover**

Envirosafe Manufacturing Corp.
7634-B Progress Circle
W. Melbourne, FL 32904

Phone: 800-800-5737
Fax: 321-733-0255
Email:
sales@envirosafemfg.com
www.envirosafemfg.com

Products that get the job done!

RUST/STAIN REMOVER™ #40-41

Application Instructions:

ALWAYS TEST ON SURFACES PRIOR TO APPLICATION!

SURFACE PREPARATION AND APPLICATION

NOTE: Wear gloves and goggles to protect from splashing.

1. Wash surface with **ENVIRO-CLEAN DEGREASER** to remove all surface dirt. Rinse with water.
2. **Water all grass and shrubs well before starting.** While damp use a SP 10A Pump Sprayer to apply Rust/Stain Remover at a rate of 200-250 sq.ft./gal.
3. Let stand for approximately 5 - 10 minutes, depending on the extent of the stain and the durability of the surface treated will determine the length of time before rinsing.
4. Scrub with a nylon bristle stiff broom or wire brush on any stubborn stains. Pressure wash off with minimum 3000 psi.

We recommend you wear OSHA Compliance chemical gloves, eye protection and rubber boots for protection.

6. Rinse with plenty of water. Always have a water source to wash off product and equipment
7. **Clean-Up:** Clean all equipment with **Enviro-Clean Degreaser Cleaner** and water.
8. Apply **Trojan Masonry Sealer** to waterproof surface and to keep stains from penetrating surface.
9. For best results use a pressure washer at a minimum of 3000 psi.
Radiator and battery acid stains are extremely difficult to remove. They will require several cleanings.

Safety: Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. All products are offered and sold subject to Envirosafe Manufacturing Corporations Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.

LIMITATIONS

Apply in good weather when air and surface temperatures are above 45 degrees Fahrenheit and surface temperature is at least 5 degrees Fahrenheit above the dew point. For optimum application properties, materials should be between 70 to 100 degrees Fahrenheit prior to application. Maintain unused material in closed containers in protected storage at 40 - 100 degrees Fahrenheit.

Do not store material in strong sunlight