



Environmentally safe products that
"Get the Job Done"

(800) 800-5737



(866) 874-8070

Product Data: **Rust/Stain Remover** **#40-41**

Product Description

A unique formulation that removes rust and stains from concrete, masonry, brick and block surfaces

Typical Uses

For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, brick pavers, stucco, cinder block or any masonry surface that has stains, particularly rust stains.

Product Advantages

**Rust Stain Remover for Masonry is: *Fast and Easy to Apply * Easy clean-up
* Water Soluble * Removes even stubborn stains * No Solvents
* Will not harm or deteriorate masonry surfaces when used properly**

Color

Orangy Yellow

Physical Constants

Specific Gravity: (H₂O=1) 1.2 @ 24 Deg C.
Solubility in Water: Soluble
Evaporation Rate: Same as water
pH: 1.0 (Corrosive)
Storage: 40-90 deg. F
Evaporation Rate: Slower than water
Viscosity: More than water
Method of Application: Sprayer

Coverage Rate

250-300 sq. ft./gallon (depends on roughness of surface & degree of staining)

Sold in

1-Gallon Bottles
5-Gallon Pails
55-Gallon Drums



Before and After cleaning with **Rust Stain Remover**

Envirosafe Manufacturing Corp.™
East Coast: 7634-B Progress * Melbourne, FL 32904
West Coast: 817 Benton Way Wenatchee, WA 98801

Web Sites
www.envirosafemfg.com
www.eco-wares.com

**Products that get the
job done!**

RUST/STAIN REMOVER #40-41

Application Instructions:

ALWAYS TEST ON SURFACES PRIOR TO APPLICATION!

LIMITATIONS: Apply in good weather when air and surface temperature are above 45 deg. F and surface temperature is at least 5 deg. F above the Dew Point. For optimum application properties, materials should be between 70-90 deg. F prior to application. Maintain unused material in closed containers in protected storage at 40-90 deg. F **out of direct sunlight.**

SURFACE PREPARATION:

NOTE: Always wear gloves, boots and goggles to protect from splashing

1. Wash surface with **ENVIRO CLEAN DEGREASER** to remove all surface dirt and grease. Rinse well with water.
2. Water surrounding grass and shrubs well before starting. While damp use a Pump Sprayer to apply **Rust/Stain Remover** at a rate of 200-250 sq. ft./gal. (Radiator and Battery Acid stains are extremely difficult to remove. They will require several cleanings)
3. Let stand approximately 5-10 minutes. The extent of the stain and the durability of the surface treated will determine the length of time before rinsing (This is why **Testing** is important)
4. Scrub with a stiff nylon bristle broom or wire brush on any stubborn stains. Pressure wash off with minimum 3000 psi. We recommend you wear OSHA Compliance chemical gloves, eye protection and rubber boots.
5. Rinse with plenty of water. Rinse equipment immediately after use.
6. **Clean-up:** Clean all equipment with **EnviroClean Degreaser** and water.
7. Apply **TROJAN MASONRY SEALER** to seal surface and to keep future stains from penetrating surface.

Safety: Safe Storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling

Notice: The technical data contained herein is true and accurate to the best of our knowledge. All products are offered and sold subject to **Envirosafe Manufacturing Corporations** Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.