

Colored Shingle Roof Coating

A specially formulated 100% acrylic coating specially designed for use on asphalt shingles. It's unique formulation provides excellent durability, superior fade resistance and a smooth low sheen that resists cracking, peeling and chipping while binding the shingles together to resist wind lift-up.



January 2011

Physical Constants

Specific Gravity: (H₂O=1) 1.8 @ 24° C.

Solubility in Water: Soluble-Use as it comes from container-Do NOT dilute

Evaporation Rate: Slower than water

pH: 8.0

Shelf Life: 1 Year in controlled area.

Method of Application: Roller or spray & back-roll

V.O.C.s: 0.42 lb/gal (50 grams/L)

Dry Time: To touch: 1-2 Hrs.

To Re-Coat: 24 Hrs.

Storage: 40-90 deg. F

COVERAGE RATE:

First Coat: 75-125 sq.ft./gal. (depends on surface roughness & method of application)

Second Coat: 100-150 sq. ft./gal.

CONTAINER SIZES:

1-Gallon Bottles

5-Gallon Pails

PRODUCT ADVANTAGES

Color Shingle Roof Coating is: Economical *

*** Non-Hazardous * Fast * Non-Flammable ***

***Easy Water Clean-up * Flexible * Durable**

TYPICAL USES

For industrial, commercial and residential use on 3 tab or dimensional shingle roofs.

For exterior use only.



Envirosafe Manufacturing / Eco-Wares, Inc.

7634-B Progress Cir.

Melbourne, Florida 32904

Toll Free (866) 874-8070



Shingle roof losing its gravel due to UV deterioration. Protect it with Color Shingle Roof Coating

Colored Shingle Roof Coating

Application Instructions

ALWAYS TEST ON SURFACES PRIOR TO APPLICATION!

Limitations: Apply in good weather when air and surface temperature are above 45°F. and surface temperature is at least 5°F. above the Dew Point. For optimum application properties, materials should be between 70-90°F. prior to application. Maintain unused material in closed containers in protected storage at 40-90°F **out of direct sunlight.** For Exterior Use only

**DO NOT TAKE INTERNALLY
KEEP OUT OF THE REACH OF
CHILDREN**



SURFACE PREPARATION:

Always test before application.

1. Good surface preparation is essential to a coating job. Remove all loose material, grease, oil dirt and biological growth. Clean area with either **EnviroClean Degreaser or Algae Mildew Cleaner.** Rinse well and allow to dry. This product is supplied at normal viscosity. Applicator should not add water
2. If the weather is hot, work in the cool of the day or in the shade of a tree. Work in strips

Safety:

Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material safety Data Sheet for this product as well as precautions contained on product labeling.

Notice: The technical data contained herein is true and accurate to the best of our knowledge. All products are offered and sold subject to EnviroSafe Manufacturing Corps. Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice

- to maintain a 'wet edge' or have several workers rolling at the same time to come across the roof together. Work the material well into all splits and spaces between shingles to bond them to one another. Use a brush to coat round the 'boots' of vent pipes.
3. Wash all tools with soap and water immediately after use. **Keep a lid on top of un-used material to prevent it from forming a skin.**