

Trojan Ultra Masonry Sealer

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard.  
9 CFR 1910.1200. Standard must be consulted for specific  
requirements.

**U. S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved OMB No. 1210-0072

**IDENTITY (AS USED ON LABEL AND LIST)**

***Trojan Ultra Masonry Sealer#60-66U***

NOTE: BLANK SPACES ARE NOT PERMITTED. IF  
ANY ITEM IS NOT APPLICABLE, OR NO  
INFORMATION IS AVAILABLE THE SPACE MUST BE  
MARKED TO INDICATE THAT.

**SECTION I**

**MANUFACTURER NAME:**

ENVIROSAFE MANUFACTURING CORP.  
7634-B Progress Cir.  
Melbourne, FL 32904

**EMERGENCY PHONE NUMBER**

CHEMTREC (800) 424-9300 Domestic  
(703) 527-3887 International

**TELEPHONE NUMBER FOR INFORMATION**

(866) 874-8070

**DATE PREPARED/UPDATED**

01/09/2002 05/17/2011

**CHEMTREC COMPANY CODE: C937**

D.O.T. Hazard Class: Non-Hazardous-Not Regulated

**SECTION II - Hazardous Ingredients / Identity Information**

Hazardous Components (Specific Chemical Identity): Common Name:	OSHA PEL	ACGH TLV	Other Limits Recommended	%
<i>No hazardous Materials to report</i>				

N/E – Not Established

N/A – Not Applicable

**SECTION III – Physical / Chemical Characteristics**

BOILING POINT:	110 <sup>0</sup> C/- 1%	SPECIFIC GRAVITY (H2O = 1):	1.01
VAPOR PRESSURE (MM HS):	N/A	FREEZING POINT:	Approx. 32 <sup>0</sup> F
VAPOR DENSITY (AIR = 1):	N/A	EVAPORATION RATE ( Butyl Acetate=1):	N/A
APPEARANCE AND ODOR:	Translucent Liquid	SOLUBILITY IN WATER:	Complete
V.O.C.: As per EPA Method 24	0.55 Lb/Gal (66.43 g/L)	SOLIDS:	19%

**SECTION IV – Fire and Explosion Hazard Data**

FLASH POINT (METHOD USED): None  
EXTINGUISHING MEDIA: Non-Flammable  
SPECIAL FIRE FIGHTING PROCEDURES: None  
UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: None  
FLAMMABLE LIMITS: None  
LEL: N/A UEL: N/A

**SECTION V – Reactivity Data**

STABILITY: STABLE:  X  UNSTABLE: \_\_\_\_\_  
INCOMPATIBLE (MATERIALS TO AVOID) ORGANICS ALKALI & ACID PRODUCTS  
HAZARDOUS DECOMPOSITIONS OR BYPRODUCTS: NE  
HAZARDOUS POLYMERIZATION : MAY OCCUR \_\_\_\_\_ WILL NOT OCCUR:  X   
CONDITIONS TO AVOID: N/A

**SECTION VI – Health Hazard Data**

ROUTE(S) OF ENTRY: INHALATION? Yes SKIN? Yes INGESTION? Yes

HEALTH HAZARDS (ACUTE AND CHRONIC):

Trojan Ultra Masonry Sealer

Breathing: Low hazard for usual industrial or commercial handling.  
Eyes: May cause slight irritation  
Skin: May cause slight irritation  
Swallowing: Expected to be low ingestion hazard.

CARCINOGENICITY: N/A      HPT? N/A      LARC MONOGRAPHS? N/A      OSHA REGULATIONS?

SIGNS AND SYMPTOMS OF EXPOSURE: Low hazard for usual industrial or commercial handling.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

EMERGENCY AND FIRST AID PROCEDURES:

1. EYES: Flush with clear water for 15 minutes.
2. SKIN: Wash affected skin areas thoroughly with soap and water.
3. INGESTION: Drink large volumes of clear water.

**FOR CASES OF INGESTION OR EYE EXPOSURE, SEEK MEDICAL ATTENTION.**

**SECTION VII – Precautions for Safe Handling and Use**

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED:

1. CONTAIN SPILL, absorb and store in DOT approved container.
2. Wash area with soap and water and rinse.

WASTE DISPOSAL METHOD: Dispose according to local regulations

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep container sealed when not in use.  
Protect from extreme changes in temperature.  
Keep product in original shipping container.  
Contact local authorities for method of proper drum disposal.  
Keep out of reach of children.  
Read product label carefully before use.

**SECTION VIII – Control Measures**

RESPIRATORY PROTECTION: Use Adequate Ventilation

VENTILATION:	LOCAL EXHAUST - YES	SPECIAL - N/A
	MECHANICAL - N/A	OTHER - N/A

PROTECTIVE WEAR:      Wear Rubber Gloves                      EYE PROTECTION:      Wear Splash Goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: It is good industrial hygiene practice to minimize skin contact.

WORK HYGIENIC PRACTICES: No other special precautionary measures should be needed under anticipated condition of use.

**SECTION IX - TRANSPORTATION INFORMATION:**

DOT (USA) STATUS: Not regulated  
TDG (CANADA) STATUS: Not regulated  
AIR - INTERNATIONAL CIVIL AVIATION ORGANIZATION ICAO - ICAO STATUS: Not regulated  
SEA - INTERNATIONAL MARITIME DANGEROUS GOODS (IMDG) - IMDG STATUS: Not regulated

**SECTION X - REGULATORY INFORMATION:**

This document has been prepared in accordance with the MSDS Requirements of the OSHA HAZARD COMMUNICATION STANDARD 29 CF4 1910. 1200

OSHA HAZARDOUS CHEMICAL(S): None  
CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER TOXIC ENFORCEMENT ACT OF 1986):  
MATERIAL(S) KNOWN TO THE STATE TO CAUSE CANCER: None materials known to the state to  
Cause adverse reproductive effect: None

Trojan Ultra Masonry Sealer

**MASSACHUSETTS SUBSTANCE LIST:** None

**NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST:** None

**TSCA Inventory Status:** Reported/Included

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR RESULTS TO BE OBTAINED FROM THE USE THEREOF. VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEETS. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSON PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN THE USE OF THIS MATERIAL.