

Envirosafe Exterior Wall Coating

A specially formulated 100% acrylic coating specially designed for use on a variety of masonry surfaces. Its' unique formulation provides excellent durability, superior fade resistance and a smooth low sheen that resists cracking, peeling and chipping while bridging hairline cracks. For exterior use only.



November 2014

Physical Constants

Specific Gravity: (H₂O=1) 1.8 @ 24° C.

Solubility in Water: Soluble-Use as it comes from container-Do NOT dilute

Evaporation Rate: Slower than water

pH: 8.0

Shelf Life: 1 Year in controlled area.

Method of Application: Roller

V.O.C.s: 0.42 lb/gal (50 grams/L)

Dry Time: To touch: 1-2 Hrs.

To Re-Coat: 24 Hrs.

Storage: 40-90 deg. F

COVERAGE RATE:

First Coat: 75-125 sq.ft./gal. (depends on surface roughness & method of application)

Second Coat: 100-175 sq. ft./gal.

CONTAINER SIZES:

1-Gallon Pail

5-Gallon Pails

PRODUCT ADVANTAGES

Envirosafe Exterior Wall Coating is:

***Economical * Non-Hazardous * Fast ***

***Non-Flammable *Easy Water Clean-up ***

***Flexible * Durable**

TYPICAL USES

For industrial, commercial and residential use on cinder block, brick, poured concrete, stucco and wood.

For exterior use only.



Envirosafe Manufacturing / Eco-Wares, Inc.

7634-B Progress Cir.

Melbourne, Florida 32904

Toll Free (866) 874-8070



Envirosafe Exterior Wall Coating

Application Instructions

ALWAYS TEST ON SURFACES PRIOR TO APPLICATION!

Limitations: Apply in good weather when air and surface temperature are above 55°F. and surface temperature is at least 5°F. above the Dew Point. For optimum application properties, materials should be between 70-90°F. prior to application. Maintain unused material in closed containers in protected storage at 40-90°F **out of direct sunlight.** For Exterior use only.

DO NOT TAKE INTERNALLY

KEEP OUT OF THE REACH OF CHILDREN

Safety: Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material safety Data Sheet for this product as well as precautions contained on product labeling.

SURFACE PREPARATION:

Always test before application.

1. Good surface preparation is essential to a coating job. Remove all loose material, grease, oil dirt and biological growth. Clean area with either **EnviroClean Degreaser, Rust Stain Remover, Easy Brick Cleaner or Algae Mildew Cleaner.** Rinse well and allow to dry. This product is supplied at normal viscosity. Applicator should not add water
2. If the weather is hot, work in the cool of the day or in the shade of a tree. Work in small areas to maintain a 'wet edge' or have several workers rolling at the same time to come across the area together. Work the material well into small hairline cracks. Use a brush to coat round small pipes and windows. Use a 3/4" nap roller on rough surfaces.
3. Wash all tools with soap and water immediately after use. **Keep a lid on top of un-used material to prevent it from forming a skin.**

Notice: The technical data contained herein is true and accurate to the best of our knowledge. All products are offered and sold subject to Envirosafe Manufacturing Corps. Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice